

T-3

METAPACE T-3

Economical fully equipped top quality printer

Technical Specifications

PRINT

Printing method	Direct thermal
Print speed	max. 250mm/sec.
Print width	max. 72mm
Resolution	7 points/mm (180 dpi)
Character size	Font A: 12 x 24, Font B: 9 x 17, Font C: 9 x 24
Sensors	Paper Near End, Paper End, Cover Open

MEDIA

Media type	Thermal paper
Paper feed	Easy paper loading
Width	79.5mm +/- 0.5mm
Roll diameter	max. 82mm
Media strength	0.062–0.075mm

ELECTRONICS

Memory	64Mbit SDRAM, 16Mbit FlashROM
Interfaces	USB 2.0 and cash drawer port (RJ12) integrated, RS232, LPT, Ethernet, WLAN (optional)
Power supply	AC 100–240V, 50/60 Hz, DC 24V, 2,5A
Barcodes	All standard 1D and 2D barcodes
Emulation	ESC / POS
Reliability	150km TPH, 1,800,000 cuts, 70,000,000 lines

SOFTWARE

Drivers	Windows 7, 8, 10 / Linux / VCOM / OPOS / JPOS / MAC
Emulation	ESC / POS
SDK	Android (starting with Version 2.2), iOS (starting with Version 5.1.1)

SPECIFICS

Standard	USB cable (A/B), power adapter + power cable (EU), CD (drivers, utilities), QSG, splash water cover, cable cover, cleaning pen, buzzer, test receipt roll
----------	---

WARRANTY

Period	5 years
--------	---------

HOUSING

Dimensions (WxHxD)	148 x 150 x 203mm
Colour	Black

CONDITIONS

Temperature	Operating: 0°C to 40°C (32°F to 104°F)
	Storage: -20°C to 60°C (-4°F to 140°F)
Humidity	Operating: 10% to 80% RH
	Storage: 10% to 90% RH

Highlights

- + Extremely reliable direct thermal printer with a 5-year warranty
- + Lightning-quick printing of slips and receipts with up to 250mm/sec.
- + Easy connection via integrated USB port
- + Versatile options: serial, parallel, Ethernet and Wi-Fi
- + Entirely out-of-the-box: just unpack and start

